

# BROOMS

## PICK-UP BROOM

Available widths 60", 72" & 84"

Direct drive Eaton® motor and intelligent design ensure years of performance.



**EATON**

Char-Lynn

Standard with 26" diameter poly/wire wafers; all-poly wafers also available.

**15-25 GPM**  
RECOMMENDED  
FLOW RATE

**DIRECT DRIVE MOTOR**  
WITH RELIEF VALVE PROTECTION

GREATER THAN  
**1500 LB**  
LOADER OPERATING CAPACITY



**OPTION: LOW PROFILE WATER KIT**

40-gallon tank provides 25 minutes of continuous runtime and drains from the bottom to use full capacity.

\*60" model uses different, non-low profile tank. Contact Virnig for more details.



**OPTION:  
GUTTER BRUSH**

Increases cleaning width by 12" and allows sweeping next to curbs and buildings.



SHOWN WITH LOW PROFILE WATER KIT OPTION



1. RECESSED & GUARDED MOTOR



2. OVERSIZED 2" GREASEABLE BEARING



3. PIN ADJUSTMENT SYSTEM TO QUICKLY SET BRISTLE HEIGHT

4. HD BUCKET WITH WEAR BARS & BOLT-ON EDGE

5. REPLACE WAFERS EASILY WITHOUT DISCONNECTING HOSES. STANDARD WITH POLY/WIRE WAFERS.

MODEL	PUB60	PUB72	PUB84
Sweeping Width (in.)	60.0	72.0	84.0
Overall Width (in.)	67.3	79.3	91.3
Overall Height (in.)		31.3	
Overall Depth (in.)		62.4	
Number of 26 Inch Diameter Wafers	29	35	41
Recommended Flow Rate (GPM)	15-25 Standard Flow Only		
Approximate Weight (lbs)	990	1120	1250
Recommended Loader Capacity	Greater than 1500 lbs <sup>1</sup>		

<sup>1</sup>Recommended Loader Capacity with Water Kit installed is 1800 lbs.