HYDRAULIC ADJUST PALLET FORK

Adjust the tines simultaneously from 8" to 38" wide without leaving the cab.



50.1" FRAME WIDTH 5500 LB

48" & 60"

GREATER THAN 1500 LB LOADER OPERATING CAPACITY







- 1. ANGLED MOUNT PLATE OPTIMIZED FOR SKID LOADER USE 4. ITA CLASS II FORGED TINES WITH
 - 5.500LB CAPACITY

2. HIGH VISIBILITY BRICKGUARD

- 5. BOLT-ON STEP INSTALLS ON EITHER SIDE
- 3. UNIQUE HOLDER DESIGN ALLOWS STANDARD TINES INSTEAD OF EXPENSIVE SHAFT STYLE TINES
- 6. HD 1 9/16" DIAMETER SHAFT

MODEL	PFHA48	PFHA60
Height: Overall w/Step / Frame (in.)	53.9 / 50.1	
Overall Height (in.)	40.1	
Tine: Length / Width / Thickness (in.)	48.0 / 4.0 / 1.5	60.0 / 4.0 / 1.5
Tine Space: Min / Max (in.)	7.8 / 38.2	
Cylinder Bore / Stroke (in.)	2.0 / 16.0	
Cylinder Pins Diameter (in.)	1.0	
Approximate Weight (lbs)	705	755
Capacity (lbs)	5500	
Recommended Loader Capacity	Greater than 1500 lbs	