

## STUMP BUCKET

Remove stumps, roots, and rocks.



1. COMPACT DEPTH MAXIMIZES LOADER BREAKOUT FORCE FOR REMOVING STUMPS
2. 3/4" x 6" WELD-ON EDGE WITH REPLACEABLE SERIES 23 TEETH (REPLACEMENT TEETH, PIN, & SHANK AVAILABLE)
3. BUCKET REINFORCED WITH LARGE GUSSET PLATES



MODEL	STMP
Overall Width (in.)	45.6
Height: Overall / Bucket (in.)	39.0 / 20.7
Overall Depth (in.)	46.3
Shovel Width: Bottom / Top (in.)	16.0 / 23.8
Space Between Teeth (in.)	3.3
Shovel Depth (in.)	29.6
Shovel Depth, With Teeth (in.)	37.3
Approximate Weight (lbs)	375
Recommended Loader Capacity	Greater than 1500 lbs

## STUMP BUCKET GRAPPLE

Remove and transport stumps, roots, and rocks.



<b>39.0"</b> JAW OPENING	<b>1-CYL</b> SINGLE JAW GRAPPLE	STANDARD WITH <b>CYLINDER GUARD</b>
--------------------------------	---------------------------------------	--

1. COMPACT DEPTH MAXIMIZES LOADER BREAKOUT FORCE TO REMOVE STUMPS
2. 3/4" x 6" WELD-ON EDGE WITH REPLACEABLE SERIES 23 TEETH (REPLACEMENT TEETH, PIN, & SHANK AVAILABLE)
3. BUCKET REINFORCED WITH LARGE GUSSET PLATES
4. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE

MODEL	STMPG
Overall Width (in.)	45.6
Height: Overall / Bucket (in.)	39.0 / 20.7
Overall Depth (in.)	46.3
Shovel Width: Bottom / Top (in.)	16.0 / 23.8
Space Between Teeth (in.)	3.3
Shovel Depth (in.)	29.6
Shovel Depth, With Teeth (in.)	37.3
Grapple Jaw Opening (in.)	39.0
Cylinder Bore / Stroke (in.)	2.0 / 8.375
Cylinder Pins / Hinge Pins Dia (in.)	1.25 / 1.563
Approximate Weight (lbs)	590
Recommended Loader Capacity	Greater than 1500 lbs