

GRAPPLES

V40 UTILITY FORK GRAPPLE

Available widths 60", 66", 72" & 78"

Single jaw grapple designed to handle manure, brush, and debris.



1.75" 1045 CSFR STEEL TINES	38" JAW OPENING	~5.4" TINE SPACING	< 2400 LB LOADER OPERATING CAP.
--------------------------------	-----------------------	--------------------------	---------------------------------------

1. NO CROSS MEMBER FOR BETTER PENETRATION
2. HIGH STRENGTH REPLACEABLE TINES
3. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE

	MODEL MGV160	MGV166	MGV172	MGV178
Overall Width (in.)	61.3	67.3	73.3	79.3
Height: Overall / Bucket (in.)	27.6 / 21.5			
Overall Depth (in.)	33.5			
Number of Tines (w/ sides)	9	10	11	12
Space Between Tines (in.)	5.4	5.3	5.2	5.1
Tine Diameter (in.)	1.75 ¹			
Cylinder Bore / Stroke (in.)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.25			
Grapple Jaw Opening (in.)	38.0			
Approximate Weight (lbs)	835	860	950	990
Recommended Loader Capacity	Less than 2400 lbs			

¹Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).

V50 TINE FORK GRAPPLE

Available widths 60", 66", 72" & 78"

High strength design for handling manure, brush, and debris.



2.0" 1045 CSFR STEEL TINES	38.2" JAW OPENING	~5.0" TINE SPACING	< 2400 LB LOADER OPERATING CAP.
-------------------------------	-------------------------	--------------------------	---------------------------------------

1. NO CROSS MEMBER FOR BETTER PENETRATION
2. 1/2" VERTICAL BRACES INSIDE BUCKET
3. HIGH STRENGTH REPLACEABLE TINES
4. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

	MODEL TBG260	TBG266	TBG272	TBG278
Overall Width (in.)	61.3	67.3	73.3	79.3
Height: Overall / Bucket (in.)	28.5 / 21.8			
Overall Depth (in.)	37.0			
Number of Tines (w/ sides)	9	10	11	12
Space Between Tines (in.)	5.1	5.0	4.9	4.8
Tine Diameter (in.)	2.0 ¹			
Cylinder Bore / Stroke (in.)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.563			
Grapple Jaw Opening (in.)	38.2			
Approximate Weight (lbs)	1040	1110	1180	1250
Recommended Loader Capacity	Less than 2400 lbs			

¹Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).