

BUCKETS

V50 MULTI-PURPOSE BUCKET (4-IN-1)

Available widths 60", 66" & 72"

Multiple functions including dozing, clamming, leveling, and bottom dumping.



AVAILABLE EDGE OPTIONS
See page 88 for additional information.



STANDARD
BOLT-ON



SERRATED
BOLT-ON



TOOTHBAR



TOOTHBAR
& BOLT-ON



WELD-ON
TEETH

37.0"
DEPTH

21.3"
HEIGHT

LESS THAN
2400 LB
LOADER OPERATING CAPACITY

1. STANDARD WITH CYLINDER GUARDS
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. 5/8" x 6" REVERSIBLE STEEL BOLT-ON EDGES
4. 3/4" x 6" WELD-ON EDGE



OPTION: HOLDING VALVE
Increases clamping force of the cylinders to secure loads.



OPTION: SIDE CUTTERS
Exclusive reversible design. Improves performance in hard, compacted soils and extends the life of the bucket sides. Not compatible with Toothbars.

MODEL	MPV60	MPV66	MPV72
Width: Overall, Straight / Inside (in.)	61.5 / 59.5	67.5 / 65.5	73.5 / 71.5
Height: Overall / Bucket / Open (in.)	29.8 / 21.3 / 46.0		
Depth: Overall / Inside (in.)	37.0 / 28.6		
Dozer Width (degrees)	59.9	65.9	71.9
Clam Opening (in.)	33.0		
Thickness: Shell / Hinge Structure (in.)	0.25 / 0.375		
Structural Wear Bars Under Bucket (1/2" x 4")	3		
Cylinder Bore / Stroke (in.)	2.5 / 8.375		
Cylinder Pins / Hinge Pins Diameter (in.)	1.25 / 1.563		
Approximate Weight (lbs)	840	915	960
Recommended Loader Capacity	Less than 2400 lbs		