

PALLET FORKS

V60 FOUR-CYLINDER PIPE PALLET FORK GRAPPLE

Four-cylinder design applies consistent pressure to secure long pipes over uneven terrain.



1. 48" OR 60" ITA CLASS II FORGED TINES
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

	MODEL	PPFG448	PPFG460
Overall Width (in.)			69.0
Overall Height: Open / Closed (in.)			62.0 / 42.5
Overall Depth (in.)		58.0	70.0
Grapple Arm Width (in.)			11.4
Grapple Arm Depth (in.)			30.4
Tine Space: Min / Max (in.)			8.9 / 49.0
Tine: Length / Width / Thickness (in.)	48.0 / 4.0 / 1.75		60.0 / 4.0 / 1.5
Cylinder Bore / Stroke (in.)		2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia. (in.)		1.25 / 1.25	
Lift Capacity (lbs)		6200	5500
Approximate Weight (lbs)		1110	1065
Recommended Loader Capacity			Greater than 1500 lbs

V60 TWO-CYLINDER PIPE PALLET FORK GRAPPLE

Two-cylinder independent clamp arms open to near-vertical for handling palletized material.



1. 48" OR 60" ITA CLASS II FORGED TINES
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

	MODEL	PPFG248	PPFG260
Overall Width (in.)			70.8
Overall Height: Open / Closed (in.)			81.4 / 40.4
Overall Depth (in.)		56.0	67.5
Grapple Arm Width (in.)			8.3
Tine Space: Min / Max (in.)			8.9 / 49.1
Tine: Length / Width / Thickness (in.)	48.0 / 4.0 / 1.75		60.0 / 4.0 / 1.5
Cylinder Bore / Stroke (in.)		2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia. (in.)		1.25 / 1.25	
Lift Capacity (lbs)		6200	5500
Approximate Weight (lbs)		920	925
Recommended Loader Capacity			Greater than 1500 lbs