

V60 MULTI-PURPOSE BUCKET (4-IN-1)

Available widths 66", 72", 78" & 84"

Heavily built bucket for dozing, clamming, leveling, and bottom dumping.



Bucket shown with optional bolt-on edge.



AVAILABLE EDGE OPTIONS
See page 88 for additional information.



STANDARD BOLT-ON



SERRATED BOLT-ON



WELD-ON TEETH

37.0"
DEPTH

21.3"
HEIGHT

GREATER THAN
2400 LB
LOADER OPERATING CAPACITY

1. STANDARD WITH CYLINDER GUARDS
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. 5/8" x 6" REVERSIBLE STEEL BOLT-ON EDGES
4. 1" x 6" WELD-ON EDGE



OPTION: HOLDING VALVE

Increases clamping force of the cylinders to secure loads.



OPTION: SIDE CUTTERS

Exclusive reversible design. Improves performance in hard, compacted soils and extends the life of the bucket sides. Not compatible with Toothbars.

MODEL	HMPV66	HMPV72	HMPV78	HMPV84
Width: Overall, Straight / Inside (in.)	67.5 / 65.5	73.5 / 71.5	79.5 / 77.5	85.5 / 83.5
Height: Overall / Bucket / Open (in.)	29.8 / 21.3 / 46.0			
Depth: Overall / Inside (in.)	37.0 / 28.5			
Dozer Width (degrees)	65.9	71.9	77.9	83.9
Clam Opening (in.)	33.0			
Thickness: Shell / Hinge Structure (in.)	0.25 / 0.5			
Structural Wear Bars Under Bucket (1/2" x 4")	4	4	5	5
Cylinder Bore / Stroke (in.)	2.5 / 8.375			
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.563			
Approximate Weight (lbs)	1045	1100	1165	1220
Recommended Loader Capacity	Greater than 2400 lbs			