

V60 ROOT RAKE GRAPPLE

Available widths 72", 78" & 84"

The toughest and largest Virnig root rake designed to dig, rake, pile, and load brush.



Known clearance issue with 72" RRG on Takeuchi® TL12, Bobcat® T66, and John Deere® 330G, 331G, 332G, 333G. No issues on other width RRGs.

0.5" GRADE 80 STEEL TINES	53.7" JAW OPENING	31.6" OVERALL DEPTH	2-CYL SINGLE-JAW GRAPPLE	GREATER THAN 2400 LB LOADER OPERATING CAPACITY
-------------------------------------	--------------------------------	----------------------------------	---------------------------------------	--

- HARD STOPS PREVENT EXCESS CYLINDER STRESS**
- SERIES 23 PIN-ON TEETH CUT INTO SOIL, DIG OUT ROCKS & ROOTS (REPLACEMENT AVAILABLE)**
- STANDARD WITH CYLINDER GUARDS**



	MODEL	RRG72	RRG78	RRG84
Overall Width (in.)		74.5	80.5	86.5
Height: Overall / Bucket (in.)			38.3 / 29.7	
Overall Depth (in.)			31.6	
Number of Teeth		7	7	8
Space Between Teeth (in.)		9.8	10.8	9.8
Space Between Tines, Grapple Jaws (in.)		10.5	11.7	10.7
Tine Thickness (in.)			0.5'	
Cylinder Bore / Stroke (in.)			2.5 / 8.375	
Cylinder Pins / Hinge Pins Dia. (in.)			1.25 / 1.563	
Grapple Jaw Opening (in.)			53.7	
Approximate Weight (lbs)		1175	1230	1315
Recommended Loader Capacity		Greater than 2400 lbs		

¹Material is Grade 80 Plate (80,000 PSI Minimum Yield Strength).