

V40 ANGLE SNOW BLADE

Available widths 60", 72", 84" & 96"



Shown with optional 2-Cylinder Hydraulic Angle



OPTION: POLY EDGE



OPTION: QUICK TACH SHOES
Helps keep the blade level.

OPTION: 1-CYLINDER & 2-CYLINDER HYDRAULIC ANGLE AVAILABLE

MANUAL & HYDRAULIC ANGLE AVAILABLE

25.8" BLADE HEIGHT

570-725 LB OVERALL WEIGHT (VARIES BY MODEL)

LESS THAN 1500 LB LOADER OPERATING CAPACITY



1. 4" SIDE-TO-SIDE OSCILLATION FOLLOWS UNEVEN SURFACES



2. ANGLE THE BLADE 28° LEFT OR RIGHT



3. TRIP EDGE PROTECTS OPERATOR & EQUIPMENT



4. 5/8" x 8" REVERSIBLE STEEL BOLT-ON EDGE ALLOWS 5 1/2" OF WEAR

	MODEL	SBS60-UT	SBS72-UT	SBS84-UT	SBS96-UT
Width: Overall, Straight / Full Angle (in.)		62.0 / 54.7	74.0 / 65.3	86.0 / 75.9	98.0 / 86.5
Overall Height (in.)			25.8		
Overall Depth, Straight (in.)			31.6		
Blade Angle (degrees)			(+/-) 28		
Moldboard Thickness (in.)			0.19		
Cutting Edge (in.)			5/8 x 8 Bolt-on		
Blade Oscillation (degrees)			(+/-) 4		
Cylinder Bore / Stroke (in.)			2.0 / 6.0		
Cylinder Pins / Hinge Pins Diameter (in.)			1.0 / 1.25		
Approximate Weight (lbs)		570 ¹	635 ¹	680 ¹	725 ¹
Recommended Loader Capacity			Less than 1500 lbs		

¹Weight with steel edge installed.