

V40 ROOT RAKE GRAPPLE

Available widths 60", 66" & 72"

Quickly dig, rake, pile, and load brush. Excels with smaller skid steers and track loaders.



Known clearance issue with 60" and 66" URG-UT on Takeuchi® TL6, TL8, TL10, TL12 and 72" URG-UT on TL12. Also, all widths on John Deere® 330G, 331G, 332G, 333G have a clearance issue.

0.375" GRADE 50
STEEL TINES

44.1"
JAW
OPENING

22.1"
OVERALL
DEPTH

2-CYL
SINGLE-JAW
GRAPPLE

LESS THAN
2200 LB
LOADER OPERATING CAPACITY

1. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
2. REPLACEABLE CAST TEETH (REPLACEMENT AVAILABLE)



MODEL	URG60-UT	URG66-UT	URG72-UT
Overall Width (in.)	61.5	67.5	73.5
Height: Overall / Bucket (in.)		34.2 / 29.3	
Overall Depth (in.)		22.1	
Number of Teeth	6	6	7
Space Between Teeth (in.)	10.2	11.4	10.2
Space Between: Tines / Grapple Jaws (in.)	5.0 / 10.9	5.0 / 12.4	5.0 / 11.1
Tine Thickness (in.)		0.375 ¹	
Cylinder Bore / Stroke (in.)		2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia. (in.)		1.25 / 1.563	
Grapple Jaw Opening (in.)		44.1	
Approximate Weight (lbs)	625	645	695
Recommended Loader Capacity		Less than 2200 lbs	

¹Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).