V50 CLOSED FRONT ROTARY BRUSH CUTTER

Available widths 60", 66", 72" & 78"

Cuts up to 4" diameter trees, and clears grass and brush for a consistent finished look.





Do not operate rotary brush cutter without a shatterproof cab on loader.

4.0"
CUT CAPACITY

60" - 78"

FOUR
CUT WIDTHS

14-42 GPM FOUR MOTOR OPTIONS STANDARD & HIGH FLOW

UP TO 225 LB FLYWHEEL WEIGHT

UP TO **1610 LB** OVERALL WEIGHT

DETAIL UNDER DECK





OPTION: REAR ROLLER Compacts chopped material and produces a better cut by limiting gouging and scalping.



OPTION: SWIVEL CASTERS 360° rotating swivel casters produce a better cut by creating a smoother ride and limiting gouging and scalping.

BRUSH CUTTERS









- 1. DIRECT DRIVE EATON® MOTOR WITH RELIEF VALVES
- 2. HYDRAULIC BRAKING STOPS FLYWHEEL WITHIN 10 SECONDS
- 3. STANDARD MOTOR GUARD & SPINDLE GUARD
- 4. CIRCULAR FLYWHEEL WITH 3 UPDRAFT BLADES BOUNCES OFF STUMPS
- 5. CHAIN CURTAIN PREVENTS FLYING DEBRIS
- 6. REPLACEABLE FRONT SKID SHOES

MODEL	RBV60	RBV66	RBV72	RBV78
Cut Width (in.)	60.0	66.0	72.0	78.0
Overall Width (in.)	66.0	72.0	78.0	84.0
Overall Height (in.)	20.9			
Overall Depth (in.)	81.8	87.8	93.8	99.8
Deck Height (in.)	8.8			
Minimum Cut Height (in.)	1.8			
Cutting Capacity, Diameter (in.)	4.0			
Deck Thickness: Top / Side (in.)	0.25 / 0.251			
Recommended Flow Rate (GPM)	14 - 25 Standard Flow, 25 - 42 High Flow			
Approximate Weight (lbs)	1180²	1325²	1435²	1540²
Recommended Loader Capacity	Greater than 1500 lbs			

¹Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength). ²High Flow Motor Options Add Approximately 70 lbs to Model Weight.