

# BRUSH CUTTERS

## V70 OPEN FRONT ROTARY BRUSH CUTTER

Available widths 72", 78" & 84"

Capable of cutting up to 8" diameter trees, this high performance brush cutter provides faster blade tip speed, quick spin up and rapid recovery.



Do not operate rotary brush cutter without a shatterproof cab on loader.

No hydraulic braking – flywheel may take minutes to come to a complete stop.

<b>8.0"</b> CUT CAPACITY	<b>72" - 84"</b> THREE CUT WIDTHS	<b>30-50 GPM</b> 2 HIGH FLOW PISTON MOTOR OPTIONS	<b>UP TO 610 LB</b> FLYWHEEL WEIGHT	<b>UP TO 2490 LB</b> OVERALL WEIGHT
-----------------------------	---	---	---	--

DETAIL UNDER DECK  
(Shown with Optional Teeth)



**OPTION:  
PRESSURE GAUGE**  
Monitor hydraulic  
operating pressure for  
max productivity.



# BRUSH CUTTERS



**1. BENT-AXIS PISTON MOTOR WITH RELIEF VALVES ENSURES RAPID FLYWHEEL SPIN UP & RECOVERY, REACHING FULL SPEED IN 13 SECONDS**

**2. STANDARD MOTOR GUARD & SPINDLE GUARD**

**3. CIRCULAR FLYWHEEL WITH 4 DOUBLE-SIDED BLADES BOUNCES OFF STUMPS**

**4. REPLACEABLE AR400 FRONT SKID SHOES & BOLT-ON AR400 BOTTOM DECK RUNNERS**

**5. SPINDLE LOW PRESSURE OIL VENT SAFEGUARDS BEARING ADAPTER SEALS IF MOTOR SEALS FAIL**

**6. CASE DRAIN CONNECTION INDICATOR PROVIDES VISUAL CONFIRMATION OF FUNCTIONING CASE DRAIN**

MODEL	PRC72	PRC78	PRC84
Cut Width (in.)	72.0	78.0	84.0
Overall Width (in.)	78.0	84.0	90.0
Overall Height (in.)		20.1	
Overall Depth (in.)	80.3	86.3	92.3
Deck Height (in.)		8.3	
Push Bar Height (in.)		23.4	
Minimum Cut Height (in.)		2.3	
Cutting Capacity, Diameter (in.)		8.0	
Deck Thickness: Top / Side (in.)		0.25 <sup>1</sup>	
Recommended Flow Rate (GPM)		30 – 50 High Flow Only	
Approximate Weight (lbs)	2155	2315	2490
Recommended Loader Capacity		Greater than 2200 lbs	
Number of Teeth (Optional)	20	24	28

<sup>1</sup>Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).